

## SAFETY DATA SHEET

## DOW CHEMICAL IBERICA S.L.

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: DOWSIL™ 813C Construction And Concrete

Silicone Black

**Revision Date:** 09.09.2020

Version: 3.0 Date of last issue: 08.04.2020

Print Date: 10.09.2020

DOW CHEMICAL IBERICA S.L. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product name: DOWSIL™ 813C Construction And Concrete Silicone Black

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Construction materials and additives

## 1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

DOW CHEMICAL IBERICA S.L. CALLE JOSE ABASCAL 56 28003 MADRID SPAIN

Customer Information Number: (091) 740 77 00

SDSQuestion@dow.com

## 1.4 EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 0034 9775 43620 **Local Emergency Contact:** 00 34 977 54 36 20 **National Institute of Toxicology:** + 34 91 562 04 20

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

## **Precautionary statements**

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

P271 Use only outdoors or in a well-ventilated area.

#### Supplemental information

Safety data sheet available on request. EUH210

**EUH208** Contains: Methyltrimethoxysilane. May produce an allergic reaction.

#### 2.3 Other hazards

This product contains no substances assessed to be PBT or vPvB at levels of 0.1% or higher.

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone elastomer

3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Classification: REGULATION (EC) No 1272/2008
CASRN 1185-55-3 EC-No. 214-685-0 Index-No.	01-2119517436-40	>= 0,6 - <= 0,66 %	 Flam. Liq 2 - H225 Skin Sens 1B - H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Page 2 of 15

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

**Ingestion:** If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of any immediate medical attention and special treatment needed Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

## SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media: None known...

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Metal oxides. Formaldehyde. Carbon oxides. Silicon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health..

## 5.3 Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment...

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

- 6.1 Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
- 6.2 Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Page 3 of 15

Silicone Black Version: 3.0

**Revision Date: 09.09.2020** 

**6.3 Methods and materials for containment and cleaning up:** Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

#### 6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

## **SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:** Do not get on skin or clothing. Avoid contact with eyes. Do not swallow. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

7.3 Specific end use(s): See the technical data sheet on this product for further information.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
Methyltrimethoxysilane	Dow IHG	TWA	7,5 ppm
	Further information: Skin S	ensitizer	

#### Recommended monitoring procedures

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with the Occupational Exposure Limits and the adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples should be analysed by an accredited laboratory.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy); European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents); European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Page 4 of 15

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods. Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods. Health and Safety Executive (HSE), United Kingdom: Methods for the Determination of Hazardous Substances.

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. L'Institut National de Recherche et de Securité, (INRS), France.

#### **Derived No Effect Level**

Methyltrimethoxysilane

#### Workers

Acute systemic effects		te systemic effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
0,38 mg/kg bw/day	25,6 mg/m3	n.a.	n.a.	0,38 mg/kg bw/day	25,6 mg/m3	n.a.	n.a.

#### Consumers

Acute systemic effects		Acute loc	cal effects	Long-term systemic effects		Long-term local effects			
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
0,3	6,25	0,26	n.a.	n.a.	0,3	6,25	0,26	n.a.	n.a.
mg/kg	mg/m3	mg/kg			mg/kg	mg/m3	mg/kg		
bw/day		bw/day			bw/day		bw/day		

#### Predicted No Effect Concentration

Methyltrimethoxysilane

Compartment	PNEC		
Fresh water	>= 1,3 mg/l		
Marine water	>= 0,13 mg/l		
Fresh water sediment	>= 1,1 mg/kg		
Marine sediment	>= 0,11 mg/kg		
Soil	>= 0,17 mg/kg		
Sewage treatment plant	> 6,9 mg/l		

#### 8.2 Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or quidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

#### **Individual protection measures**

Eye/face protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

## **Skin protection**

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber

Page 5 of 15

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

> ("nitrile" or "NBR"), Ethyl vinyl alcohol laminate ("EVAL"), Polyvinyl alcohol ("PVA"), Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or quidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Use the following CE approved air-purifying respirator: Organic vapor cartridge, type A (boiling point >65 °C, meeting standard EN 14387).

#### **Environmental exposure controls**

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties **Appearance**

Physical state paste Color black Odor none

**Odor Threshold** No data available На Not applicable Melting point/range No data available Freezing point No data available Boiling point (760 mmHg) Not applicable

Product name: DOWSIL™ 813C Construction And Concrete

Revision Date: 09.09.2020

Silicone Black

Version: 3.0

Flash point closed cup >100 °C

Evaporation Rate (Butyl Acetate Not applicable

= 1)

..

Flammability (solid, gas)

Lower explosion limit

Upper explosion limit

Vapor Pressure

Relative Vapor Density (air = 1)

Not classified as a flammability hazard

No data available

Not applicable

No data available

Relative Density (water = 1) 1,50

Water solubility

No data available

Partition coefficient: n
No data available

octanol/water

Auto-ignition temperature

Decomposition temperature

Dynamic Viscosity

Kinematic Viscosity

Explosive properties

No data available
No data available
Not applicable
Not applicable
Not explosive

**Oxidizing properties** The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weightNo data availableParticle sizeNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

## **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity: Not classified as a reactivity hazard.

**10.2 Chemical stability:** Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents.

10.4 Conditions to avoid: None known.

10.5 Incompatible materials: Oxidizing agents

10.6 Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde.

## SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

#### 11.1 Information on toxicological effects

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

### Information on likely routes of exposure

Eve contact, Skin contact, Ingestion.

## Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

#### Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. May cause abdominal discomfort or diarrhea.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 2 000 mg/kg Estimated.

#### Information for components:

#### Methyltrimethoxysilane

LD50, Rat, male and female, 11 685 mg/kg

## **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rabbit, > 2 000 mg/kg Estimated.

## Information for components:

#### **Methyltrimethoxysilane**

LD50, Rabbit, male and female, > 9 500 mg/kg OECD 402 or equivalent

#### Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

## Information for components:

#### Methyltrimethoxysilane

LC50, Rat, male and female, 6 Hour, vapour, > 7605 ppm OECD Test Guideline 403

#### Skin corrosion/irritation

Based on information for component(s): Brief contact is essentially nonirritating to skin.

May cause drying and flaking of the skin.

## Information for components:

Page 8 of 15

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

#### Methyltrimethoxysilane

Brief contact may cause slight skin irritation with local redness.

#### Serious eve damage/eve irritation

Based on information for component(s): May cause slight temporary eye irritation.

May cause mild eye discomfort.

#### Information for components:

#### Methyltrimethoxysilane

May cause slight temporary eye irritation. Corneal injury is unlikely.

#### Sensitization

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant information found.

## Information for components:

#### Methyltrimethoxysilane

For skin sensitization:

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

## **Specific Target Organ Systemic Toxicity (Single Exposure)**

Available data are inadequate to determine single exposure specific target organ toxicity.

#### Information for components:

#### Methyltrimethoxysilane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

## Information for components:

## Methyltrimethoxysilane

May be harmful if swallowed and enters airways.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

## Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data for the component(s), repeated exposures are not anticipated to cause significant adverse effects.

Page 9 of 15

Product name: DOWSIL™ 813C Construction And Concrete Revision Date: 09.09.2020

Silicone Black Version: 3.0

#### Information for components:

## **Methyltrimethoxysilane**

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

#### Carcinogenicity

Contains a component(s) that is/are not expected to be bioavailable due to the physical state of the material under normal handling and processing conditions.

## Information for components:

## **Methyltrimethoxysilane**

No relevant data found.

#### **Teratogenicity**

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

## Information for components:

## **Methyltrimethoxysilane**

Did not cause birth defects or any other fetal effects in laboratory animals.

#### Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies. Contains component(s) which did not interfere with fertility in animal studies.

#### Information for components:

## **Methyltrimethoxysilane**

In animal studies, did not interfere with reproduction.

#### Mutagenicity

In vitro genetic toxicity studies were negative for component(s) tested. Contains component(s) which were negative in some animal genetic toxicity studies and positive in others. Positive findings were observed only at doses which produced significant inflammation.

## Information for components:

#### Methyltrimethoxysilane

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicological information appears in this section when such data is available.

## 12.1 Toxicity

#### Methyltrimethoxysilane

Acute toxicity to fish

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 110 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 122 mg/l, OECD Test Guideline 202

#### Acute toxicity to algae/aguatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 3,6 mg/l, OECD Test Guideline 201

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, >= 3,6 mg/l, OECD Test Guideline 201

#### Toxicity to bacteria

EC10, activated sludge, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

## Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 28 d, number of offspring, >= 10 mg/l

## 12.2 Persistence and degradability

## Methyltrimethoxysilane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

**Biodegradation:** 54 % Exposure time: 28 d

Method: Regulation (EC) No. 440/2008, Annex, C.4-A

#### 12.3 Bioaccumulative potential

#### Methyltrimethoxysilane

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0,82 Estimated.

#### 12.4 Mobility in soil

#### Methyltrimethoxysilane

No relevant data found.

#### 12.5 Results of PBT and vPvB assessment

#### Methyltrimethoxysilane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### 12.6 Other adverse effects

#### Methyltrimethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Page 11 of 15

Product name: DOWSIL™ 813C Construction And Concrete Revision Date: 09.09.2020 Silicone Black Version: 3.0

## SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

#### SECTION 14: TRANSPORT INFORMATION

#### Classification for ROAD and Rail transport (ADR/RID):

**14.1 UN number** Not applicable

**14.2 UN proper shipping name** Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

**14.5** Environmental hazards Not considered environmentally hazardous based on

available data.

**14.6** Special precautions for user No data available.

## Classification for SEA transport (IMO-IMDG):

**14.1 UN number** Not applicable

**14.2 UN proper shipping name** Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

**14.5** Environmental hazards Not considered as marine pollutant based on available data.

**14.6** Special precautions for user No data available.

14.7 Transport in bulk according to Annex I or II of MARPOL

73/78 and the IBC or IGC

Consult IMO regulations before transporting ocean bulk

Code

## Classification for AIR transport (IATA/ICAO):

**14.1 UN number** Not applicable

**14.2 UN proper shipping name** Not regulated for transport

14.3 Transport hazard class(es) Not applicable
14.4 Packing group Not applicable
14.5 Environmental hazards Not applicable

Product name: DOWSIL™ 813C Construction And Concrete Revision Date: 09.09.2020 Silicone Black Version: 3.0

#### **14.6** Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

#### **SECTION 15: REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## REACh Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

## **SECTION 16: OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.H317 May cause an allergic skin reaction.

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.

#### Revision

Identification Number: 4067950 / A282 / Issue Date: 09.09.2020 / Version: 3.0

Page 13 of 15

**Revision Date: 09.09.2020** Silicone Black Version: 3.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

#### Legend

Dow IHG	Dow Industrial Hygiene Guideline
TWA	Time weighted average
Flam. Liq.	Flammable liquids
Skin Sens.	Skin sensitisation

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS -Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG -International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL IBERICA S.L. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his

Product name: DOWSIL™ 813C Construction And Concrete Revision Date: 09.09.2020 Silicone Black Version: 3.0

activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

Page 15 of 15