

SAFETY DATA SHEET

DOW CHEMICAL IBERICA S.L.

Safety Data Sheet according to Reg. (EU) 2020/878

Product name: DOWSIL™ 3363 Insulating Glass Sealant

Catalyst Black

Version: 8.0

Date of last issue: 09.02.2024

Print Date: 22.02.2024

Revision Date: 20.02.2024

DOW CHEMICAL IBERICA S.L. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Black

UFI: SPT8-A1JF-800N-JD9D

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Formulation or re-packing: Formulation & (re)packing of substances and mixtures. Use at industrial sites: Use in sealants.

1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

DOW CHEMICAL IBERICA S.L. CALLE JOSE ABASCAL 56 28003 MADRID SPAIN

Customer Information Number: (091) 740 77 00

SDSQuestion@dow.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 0034 9775 43620 **Local Emergency Contact:** 00 34 977 54 36 20 **National Institute of Toxicology:** + 34 91 562 04 20

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Skin irritation - Category 2 - H315
Serious eye damage - Category 1 - H318
Skin sensitisation - Category 1 - H317
Specific target organ toxicity - repeated exposure - Category 2 - Oral - H373
For the full text of the H-Statements mentioned in this Section, see Section 16.

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024

Black Version: 8.0

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms







Signal word: DANGER

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H373 May cause damage to organs (Bladder) through prolonged or repeated exposure if

swallowed.

Precautionary statements

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER

and/or doctor.

P314 Get medical advice or attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Contains N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine; Bis(trimethoxysilyl)hexane; 3-

aminopropyltriethoxysilane: Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

2.3 Other hazards

This product contains octamethylcyclotetrasiloxane (D4) that has been identified by the Member State Committee of ECHA as fulfilling the PBT and vPvB criteria laid down in Annex XIII to Regulation (EC) No 1907/2006. See Section 12 for additional information.

Endocrine disrupting properties

Environment: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

at levels of 0.1% or higher.

Human Health: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Page 2 of 52

Chemical nature: Silicone Sealant

3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN 474530-85-3 EC-No. 610-348-0 Index-No.	-	>= 10,0 - <= 15,0 %	Aminopropyltriethox ysilane Rxn with Glycidoxypropyltrim ethoxysilane and Methyltrimethoxysil ane	Eye Irrit. 2; H319 Acute toxicity estimate Acute dermal toxicity: > 2 000 mg/kg
CASRN 1760-24-3 EC-No. 217-164-6 Index-No.	01-2119970215-39	>= 4,6 - <= 5,3 %	N-(3- (Trimethoxysilyl) propyl)-1,2- ethanediamine	Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT RE 2; H373 (Respiratory Tract) Acute toxicity estimate Acute oral toxicity: 2 295 mg/kg Acute inhalation toxicity: 1,49 - 2,44 mg/l, 4 Hour, dust/mist Acute dermal toxicity: > 2 000 mg/kg
CASRN 87135-01-1 EC-No. 617-969-6 Index-No.	01-2119420448-41	>= 2,9 - <= 4,2 %	Bis(trimethoxysilyl)h exane	STOT RE 1; H372 (Bladder) Acute toxicity estimate Acute oral toxicity: > 2 000 mg/kg Acute inhalation toxicity: > 0,042 mg/l, 4 Hour, vapour
CASRN 919-30-2 EC-No. 213-048-4 Index-No. 612-108-00-0	_	>= 0,7 - <= 1,1 %	3- aminopropyltriethox ysilane	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 1 479 mg/kg 2 665 mg/kg Acute inhalation toxicity: > 5 ppm, 6 Hour, vapour > 16 ppm, 6 Hour, vapour > 7,35 mg/l, 4 Hour,

Version: 8.0

				Aerosol
				Acute dermal toxicity: 4 041 mg/kg
CASRN 67-56-1 EC-No. 200-659-6 Index-No. 603-001-00-X	_	>= 0,03 - <= 0,91 %	methanol	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 STOT SE 1; H370 (Eyes, Central nervous system)
				specific concentration limit STOT SE 1; H370 >= 10 % STOT SE 2; H371 3 - < 10 %
				Acute toxicity estimate Acute oral toxicity: > 5 000 mg/kg 340 mg/kg Acute inhalation toxicity: 3 mg/l, 4 Hour, vapour Acute dermal toxicity: 15 800 mg/kg
CASRN 68928-76-7 EC-No. 273-028-6 Index-No.	01-2120770324-57	>= 0,05 - <= 0,19 %	dimethylhexanoyl)o	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 3; H412
_				Acute toxicity estimate Acute oral toxicity: 892 mg/kg Acute dermal toxicity: > 2 000 mg/kg
CASRN 1112-39-6 EC-No.	_	>= 0,11 - <= 0,19 %	Dimethyldimethoxy silane	Flam. Liq. 2; H225 Repr. 2; H361
214-189-4 Index-No.				Acute toxicity estimate Acute oral toxicity: > 2 000 - 5 000 mg/kg Acute inhalation toxicity: > 4,7 mg/l, 4 Hour, vapour
CASRN 556-67-2 EC-No. 209-136-7 Index-No.	_	>= 0,022 - <= 0,039	octamethylcyclotetr asiloxane [D4]	Flam. Liq. 3; H226 Repr. 2; H361f Aquatic Chronic 1; H410
014-018-00-1				M-Factor (Chronic aquatic toxicity): 10
				Acute toxicity estimate

Revision Date: 20.02.2024 Version: 8.0

Product name: DOWSIL *** 3363 Insulating Glass Sealant Catalyst	Revision Date: 20.02.2024
Black	Version: 8.0

				Acute oral toxicity: > 4 800 mg/kg Acute inhalation toxicity: 36 mg/l, 4 Hour, dust/mist Acute dermal toxicity:
				> 2 400 mg/kg
Substances with	n a workplace exposu	ıre limit		
CASRN	01-2119517436-40	>= 10,0 - <= 15,0 %	,	Flam. Liq. 2; H225
1185-55-3			ane	A
EC-No.				Acute toxicity estimate
214-685-0 Index-No.				Acute oral toxicity:
muex-No.				11 685 mg/kg
_				Acute inhalation toxicity: > 7605 ppm, 6 Hour,
				vapour
				Acute dermal toxicity:
				> 9 500 mg/kg

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation or rash occurs. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be immediately available.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

4.2 Most important symptoms and effects, both acute and delayed:

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause damage to organs through prolonged or repeated exposure if swallowed.

Revision Date: 20.02.2024 Black Version: 8.0

4.3 Indication of any immediate medical attention and special treatment needed Notes to physician: Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If burn is present, treat as any thermal burn, after decontamination. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. No specific antidote.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical. Water spray.

Unsuitable extinguishing media: None known...

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides. Nitrogen oxides (NOx). Formaldehyde.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to

5.3 Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers.. Evacuate area.. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage...

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus.. Use personal protective equipment..

SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
- **6.2 Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- 6.3 Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

Revision Date: 20.02.2024 Black Version: 8.0

which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Do not get in eyes. Keep container tightly closed. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied.

Use with local exhaust ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

7.2 Conditions for safe storage, including any incompatibilities: Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

7.3 Specific end use(s): See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
N-(3-(Trimethoxysilyl)	Dow IHG		See Further information
propyl)-1,2-ethanediamine			
	Further information: Skin S	ensitizer	
3-aminopropyltriethoxysilane	Dow IHG	TWA	0,5 mg/m3
methanol	ACGIH	TWA	200 ppm
	Further information: Skin: D	Danger of cutaneous absorption	on
	ACGIH	STEL	250 ppm
	Further information: Skin: D	Danger of cutaneous absorption	on
	2006/15/EC	TWA	260 mg/m3 200 ppm
	Further information: Indicat through the skin	ive; skin: Identifies the possil	bility of significant uptake
	ES VLA	VLA-ED	266 mg/m3 200 ppm
	Further information: dermal	route: Skin	
Bis[(2-ethyl-2,5-	ACGIH	TWA	0,1 mg/m3 , Tin
dimethylhexanoyl)oxy](dimet			
hyl)stannane			
	Further information: A4: No cutaneous absorption	t classifiable as a human card	cinogen; Skin: Danger of
	ACGIH	STEL	0,2 mg/m3 , Tin

Black			Version: 8.0
			•

	Further information: A4: No cutaneous absorption	Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of cutaneous absorption					
	ES VLA VLA-ED 0,1 mg/n						
	Further information: dermal	route: Skin					
	ES VLA	VLA-EC	0,2 mg/m3 , Tin				
	Further information: dermal	route: Skin					
octamethylcyclotetrasiloxane	US WEEL	TWA	10 ppm				
[D4]							
Methyltrimethoxysilane	Dow IHG	TWA	7,5 ppm				
Ethanol	ACGIH	TWA	1 000 ppm				
	Further information: URT in	r: Upper Respiratory Tract irri	tation				
	ACGIH	STEL	1 000 ppm				
	Further information: URT in	r: Upper Respiratory Tract irri	tation				
	ES VLA	VLA-EC	1 910 mg/m3 1 000				
			ppm				

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:, Methanol., Ethanol

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
methanol	67-56-1	Methanol	Urine	End of workday	15 mg/l	ES VLB
		Methanol	Urine	End of shift (As soon as possible after exposure	15 mg/l	ACGIH BEI
				exposure ceases)		

Recommended monitoring procedures

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with the Occupational Exposure Limits and the adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples should be analysed by an accredited laboratory.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy); European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents); European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents). Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods. Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods. Health and Safety Executive (HSE), United Kingdom: Methods for the Determination of Hazardous Substances.

Revision Date: 20.02.2024

Revision Date: 20.02.2024 Black Version: 8.0

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany. L'Institut National de Recherche et de Securité, (INRS), France.

Derived No Effect Level

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Workers

Acute systemic effects		Acute loc	cal effects	•	n systemic ects	Long-term	local effects
Dermal	Inhalation	Dermal Inhalation		Dermal	Inhalation	Dermal	Inhalation
14,5	25 mg/m3	n.a.	n.a. n.a.		25 mg/m3	n.a.	n.a.
mg/kg				mg/kg			
bw/day				bw/day			

Consumers

Acute systemic effects		al effects	Long-term systemic effects			Long-term local effects			
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Dermal Inhalation Oral			Inhalation
n.a.	n.a. 1 mg/kg bw/day		n.a.	n.a.	n.a.	n.a.	1 mg/kg bw/day	n.a.	n.a.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Workers

Acute syste	emic effects	Acute loc	cal effects	•	n systemic ects	Long-term	local effects
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	5,36 mg/m3	n.a.	n.a.	n.a.	0,6 mg/m3

Consumers

Consum	JI 3								
Acute systemic effects		Acute lo	cal effects	Long-te	rm systemi	c effects		rm local ects	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	4 mg/m3	n.a.	n.a.	n.a.	n.a.	0,1
									mg/m3

Bis(trimethoxysilyI)hexane

Workers

Acute systemic effects		Acute lo	cal effects	Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	0,03	0,2 mg/m3	n.a.	n.a.
				mg/kg			
				bw/day			

Consumers

OUTIONITIE	,. •								
Acute	systemic e	effects	Acute lo			Long-term systemic effects		term local fects	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	0,013 mg/kg bw/day	n.a.	n.a.

Page 9 of 52

Revision Date: 20.02.2024 Black Version: 8.0

3-aminopropyltriethoxysilane

Workers

Acute syste	emic effects	Acute loc	al effects	•	n systemic ects	Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	2 mg/kg bw/day	14 mg/m3	n.a.	n.a.

Consumers

Oonoanic	,, 0									
Acute	systemic e	effects	Acute loc	al effects	Long-term systemic effects			S Long-term systemic effects Long-ter effe		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation	
n.a.	n.a.	n.a.	n.a.	n.a.	1 mg/kg	3,5	1 mg/kg	n.a.	n.a.	
					bw/day	mg/m3	bw/day			

methanol

Workers

Acute systemic effects		Acute loc	cal effects	Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
20 mg/kg	130	n.a.	130	20 mg/kg	130	n.a.	130 mg/m3
bw/day	mg/m3		mg/m3	bw/day	mg/m3		

Consumers

Oonoame										
Acute	systemic e	effects	Acute loc	al effects	Long-term systemic effects			Long-term local effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation	
4 mg/kg	26	4 mg/kg	n.a.	26	4 mg/kg	26	4 mg/kg	n.a.	26	
bw/day	mg/m3	bw/day		mg/m3	bw/day	mg/m3	bw/day		mg/m3	

Dimethyldimethoxysilane

Workers

11011010								
Acute systemic effects		Acute local effects		_	n systemic ects	Long-term local effects		
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	
7,44	88,4	n.a.	n.a.	7,44	88,4	n.a.	n.a.	
mg/kg	mg/m3			mg/kg	mg/m3			
bw/day				bw/day				

Consumers

Acute	systemic e	effects	Acute lo	cal effects	Long-term systemic effects		Long-term loc effects		
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	5,21 mg/kg bw/day	n.a.	n.a.

octamethylcyclotetrasiloxane [D4]

Workers

Acute syste	emic effects	Acute loc	cal effects	•	n systemic ects	Long-term	local effects
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation

Page 10 of 52

Revision Date: 20.02.2024 Version: 8.0

n.a. n.a.	n.a.	n.a.	n.a.	73 mg/m3	n.a.	73 mg/m3
-----------	------	------	------	----------	------	----------

Consumers

Acute	systemic e	effects	Acute lo	cal effects	Long-term systemic effects		•	rm local ects	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	13 mg/m3	3,7 mg/kg bw/day	n.a.	13 mg/m3

Methyltrimethoxysilane

Workers

Acute syste	Acute systemic effects		al effects	Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal Inhalatio		Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	3,6 mg/m3	25,6 mg/m3	n.a.	n.a.

Consumers

Acute systemic effects		Acute local effects		Long-term systemic effects		Long-term local effects			
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	7,2	6,25	0,26	n.a.	n.a.
					mg/m3	mg/m3	mg/m3		

Predicted No Effect Concentration

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Compartment	PNEC
Fresh water	0,13 mg/l
Marine water	0,013 mg/l
Fresh water sediment	0,1 mg/kg
Marine sediment	0,01 mg/kg
Soil	0,016 mg/kg
Sewage treatment plant	>= 100 mg/l

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Compartment	PNEC
Fresh water	0,05 mg/l
Intermittent use/release	0,072 mg/l
Marine water	0,005 mg/l
Sewage treatment plant	20 mg/l
Fresh water sediment	0,181 mg/kg dry weight
	(d.w.)
Marine sediment	0,018 mg/kg dry weight
	(d.w.)
Soil	0,00687 mg/kg dry weight
	(d.w.)

Bis(trimethoxysilyI)hexane

Page 11 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Compartment	PNEC
Fresh water	0,074 mg/l
Intermittent use/release	0,74 mg/l
Marine water	0,0074 mg/l
Sewage treatment plant	74 mg/l
Fresh water sediment	0,27 mg/l
Marine sediment	0,027 mg/l
Soil	0,01 mg/l

3-aminopropyltriethoxysilane

Compartment	PNEC
Fresh water	0,5 mg/l
Intermittent use/release	2,05 mg/l
Marine water	0,05 mg/l
Fresh water sediment	1,8 mg/kg
Marine sediment	0,18 mg/kg
Soil	0,069 mg/kg
Sewage treatment plant	0,81 mg/l

Dimethyldimethoxysilane

Compartment	PNEC		
Fresh water	0,24 mg/l		
Marine water	0,024 mg/l		
Fresh water sediment	0,22 mg/kg		
Marine sediment	0,022 mg/kg		
Soil	0,053 mg/kg		
Sewage treatment plant	10 mg/l		

octamethylcyclotetrasiloxane [D4]

Compartment	PNEC
Fresh water	0,0015 mg/l
Marine water	0,00015 mg/l
Sewage treatment plant	10 mg/l
Fresh water sediment	3 mg/kg dry weight (d.w.)
Marine sediment	0,3 mg/kg dry weight (d.w.)
Soil	0,84 mg/kg dry weight (d.w.)
Oral	41 mg/kg food

Methyltrimethoxysilane

Compartment	PNEC
Fresh water sediment	0,73 mg/kg
Marine sediment	0,073 mg/kg
Soil	0,03 mg/kg

8.2 Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Page 12 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024
Black Version: 8.0

Individual protection measures

Eye/face protection: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state paste
Color black
Odor alcohol-like

Odor Threshold No data available

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024
Black Version: 8.0

pH Not applicable, substance/mixture is non-soluble (in water)

Melting point/freezing point

Melting point/range No data available
Freezing point not determined
Boiling point or initial boiling point and boiling range

Boiling point (760 mmHg) Not applicable
Flash point Not applicable

Flammability (solid, gas) Not classified as a flammability hazard

Flammability (liquids)

Lower explosion limit

Upper explosion limit

Vapor Pressure

Relative Vapor Density (air = 1)

Not applicable, solid

No data available

Not applicable

Not applicable

Relative Density (water = 1) 1,05

Density 1,05 g/cm3

Solubility(ies)

Water solubility insoluble

Partition coefficient: n- not determined

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableKinematic ViscosityNot applicable

Particle characteristics

Particle size No data available

9.2 Other information

Molecular weightNo data availableDynamic ViscosityNot applicableExplosive propertiesNot explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Self-heating substances The substance or mixture is not classified as self heating.

Evaporation Rate (Butyl Acetate Not applicable

= 1)

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

10.2 Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents.

Revision Date: 20.02.2024 Black Version: 8.0

10.4 Conditions to avoid: None known.

10.5 Incompatible materials: Avoid contact with oxidizing materials.

10.6 Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde. Methanol. Ethanol.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data are available.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

Acute Toxicity Endpoints:

Acute oral toxicity

Information for the Product:

Very low toxicity if swallowed. Swallowing may result in irritation of the mouth, throat, and gastrointestinal tract.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, > 5 000 mg/kg Estimated.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Single dose oral LD50 has not been determined.

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

LD50, Rat, male and female, 2 295 mg/kg OPPTS 870.1100

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Page 15 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Bis(trimethoxysilyl)hexane

LD50, Rat, male and female, > 2 000 mg/kg. No deaths occurred at this concentration.

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

3-aminopropyltriethoxysilane

LD50, Rat, female, 1 479 mg/kg

LD50, Rat, male, 2 665 mg/kg

methanol

Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart. Effects may be delayed. LD50, Rat, > 5 000 mg/kg

Lethal Dose, Humans, 340 mg/kg Estimated.

Lethal Dose, Humans, 29 - 237 ml Estimated.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

LD50, Rat, male and female, 892 mg/kg OECD 401 or equivalent

Dimethyldimethoxysilane

LD50, Rat, > 2 000 - 5 000 mg/kg

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

octamethylcyclotetrasiloxane [D4]

LD50, Rat, male, > 4 800 mg/kg No deaths occurred at this concentration.

Methyltrimethoxysilane

LD50, Rat, male and female, 11 685 mg/kg

This substance may hydrolyze to release Methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Acute dermal toxicity

Information for the Product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024

Black Version: 8.0

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, > 2 000 mg/kg Estimated.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Based on data from similar materials LD50, Rabbit, > 2 000 mg/kg

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

LD50, Rabbit, male and female, > 2 000 mg/kg No deaths occurred at this concentration.

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

Bis(trimethoxysilyl)hexane

The dermal LD50 has not been determined.

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

3-aminopropyltriethoxysilane

Based on product testing: LD50, Rabbit, male and female, 4 041 mg/kg

<u>methanol</u>

Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death. LD50, Rabbit, 15 800 mg/kg

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

LD50, Rat, > 2000 mg/kg

Dimethyldimethoxysilane

The dermal LD50 has not been determined.

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

Page 17 of 52

Revision Date: 20.02.2024 Black Version: 8.0

octamethylcyclotetrasiloxane [D4]

LD50, Rat, male and female, > 2 400 mg/kg No deaths occurred at this concentration.

Methyltrimethoxysilane

LD50, Rabbit, male and female, > 9 500 mg/kg OECD 402 or equivalent

This substance may hydrolyze to release Methanol. Effects of methanol are the same as observed via oral and inhalation exposure and include central nervous system (CNS) depression, visual impairment up to blindness, metabolic acidosis, with effects on organ systems such as liver, kidneys and heart, even death.

Acute inhalation toxicity

Information for the Product:

Prolonged excessive exposure may cause adverse effects. Vapor from heated material may cause respiratory irritation. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

As product: The LC50 has not been determined.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

The LC50 has not been determined.

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

LC50, Rat, male and female, 4 Hour, dust/mist, 1,49 - 2,44 mg/l OECD Test Guideline 403

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

Bis(trimethoxysilyI)hexane

LC50, Rat, male and female, 4 Hour, vapour, > 0,042 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

3-aminopropyltriethoxysilane

Based on product testing: LC50, Rat, male, 6 Hour, vapour, > 5 ppm No deaths occurred at this concentration.

Based on product testing: LC50, Rat, female, 6 Hour, vapour, > 16 ppm No deaths occurred at this concentration.

Page 18 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Based on product testing: LC50, Rat, male and female, 4 Hour, Aerosol, > 7,35 mg/l

Easily attainable vapor concentrations may cause serious adverse effects, even death. At lower concentrations: May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness. progressing to incoordination and unconsciousness. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death. Effects may be delayed.

LC50, Rat, 4 Hour, vapour, 3 mg/l

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

As product: The LC50 has not been determined.

Dimethyldimethoxysilane

LC50, Rat, 4 Hour, vapour, > 4,7 mg/l

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

octamethylcyclotetrasiloxane [D4]

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

Methyltrimethoxysilane

LC50, Rat, male and female, 6 Hour, vapour, > 7605 ppm OECD Test Guideline 403

This substance may hydrolyze to release Methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

Skin corrosion/irritation

Causes skin irritation.

Information for the Product:

Based on information for component(s):

Brief contact may cause moderate skin irritation with local redness.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Brief contact may cause slight skin irritation with local redness.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Brief contact may cause moderate skin irritation with local redness.

Bis(trimethoxysilyl)hexane

Essentially nonirritating to skin.

Page 19 of 52

Revision Date: 20.02.2024 Black Version: 8.0

3-aminopropyltriethoxysilane

Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

methanol

Prolonged contact may cause slight skin irritation with local redness.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Brief contact may cause skin irritation with local redness.

Dimethyldimethoxysilane

Brief contact is essentially nonirritating to skin.

octamethylcyclotetrasiloxane [D4]

Brief contact is essentially nonirritating to skin.

Methyltrimethoxysilane

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

Causes serious eye damage.

Information for the Product:

Based on information for component(s):

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

May cause moderate eye irritation.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Bis(trimethoxysilyI)hexane

Essentially nonirritating to eyes.

3-aminopropyltriethoxysilane

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Vapor or mist may cause eye irritation.

methanol

May cause eye irritation.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

May cause slight eye irritation.

Page 20 of 52

Revision Date: 20.02.2024 Black Version: 8.0

May cause slight temporary corneal injury.

Dimethyldimethoxysilane

Essentially nonirritating to eyes.

octamethylcyclotetrasiloxane [D4]

Essentially nonirritating to eyes.

Methyltrimethoxysilane

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Sensitization

For skin sensitization:

May cause an allergic skin reaction.

Information for the Product:

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Bis(trimethoxysilyI)hexane

For skin sensitization:

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

3-aminopropyltriethoxysilane

Has caused allergic skin reactions when tested in guinea pigs.

Page 21 of 52

Revision Date: 20.02.2024 Black Version: 8.0

For respiratory sensitization:

No relevant data found.

methanol

For skin sensitization: No relevant data found.

For respiratory sensitization:

No relevant data found.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Dimethyldimethoxysilane

For similar material(s):

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

octamethylcyclotetrasiloxane [D4]

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Methyltrimethoxysilane

For skin sensitization:

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Information for the Product:

Product test data not available.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Available data are inadequate to determine single exposure specific target organ toxicity.

Bis(trimethoxysilyl)hexane

Page 22 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

3-aminopropyltriethoxysilane

Material is corrosive. Material is not classified as a respiratory irritant; however, upper respiratory tract irritation or corrosivity may be expected.

methanol

Causes damage to organs.

Target Organs: Eyes, Central nervous system

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Available data are inadequate to determine single exposure specific target organ toxicity.

Dimethyldimethoxysilane

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

octamethylcyclotetrasiloxane [D4]

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

<u>Methyltrimethoxysilane</u>

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Aspiration Hazard

Information for the Product:

Based on physical properties, not likely to be an aspiration hazard.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and <u>Methyltrimethoxysilane</u>

Based on available information, aspiration hazard could not be determined.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Based on available information, aspiration hazard could not be determined.

Bis(trimethoxysilyI)hexane

Material is not classified as an aspiration hazard based on insufficient data, however materials with low viscosity may be aspirated into the lungs during ingestion or vomiting.

3-aminopropyltriethoxysilane

Aspiration into the respiratory system may occur during ingestion or vomiting. Due to corrosivity, tissue damage or lung injury may occur.

methanol

May be harmful if swallowed and enters airways.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Based on physical properties, not likely to be an aspiration hazard.

Dimethyldimethoxysilane

Page 23 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Based on physical properties, not likely to be an aspiration hazard.

octamethylcyclotetrasiloxane [D4]

Material is not classified as an aspiration hazard based on insufficient data, however materials with low viscosity may be aspirated into the lungs during ingestion or vomiting.

Methyltrimethoxysilane

Material is not classified as an aspiration hazard based on insufficient data, however materials with low viscosity may be aspirated into the lungs during ingestion or vomiting.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

Specific Target Organ Systemic Toxicity (Repeated Exposure)

May cause damage to organs (Bladder) through prolonged or repeated exposure if swallowed.

Information for the Product:

Product test data not available.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

In animals, effects have been reported on the following organs: Respiratory tract.

Bis(trimethoxysilyl)hexane

In animals, effects have been reported on the following organs:

Bladder

In animals, effects have been reported on the following organs:

Liver

Stomach

Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

Kidney effects have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

3-aminopropyltriethoxysilane

In animals, effects have been reported on the following organs:

Liver.

methanol

Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

In animals, effects have been reported on the following organs:

Page 24 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Blood

Kidnev

Liver

Immune system.

Dimethyldimethoxysilane

In animals, effects have been reported on the following organs:

Liver

Male reproductive organs.

This material contains dimethyldimethoxysilane. Repeated exposure in rats to dimethyldimethoxysilane resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

octamethylcyclotetrasiloxane [D4]

In animals, effects have been reported on the following organs:

Kidney.

Liver.

Respiratory tract.

Female reproductive organs.

Methyltrimethoxysilane

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Information for the Product:

Product test data not available.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

No relevant data found.

Bis(trimethoxysilyI)hexane

No relevant data found.

3-aminopropyltriethoxysilane

Did not cause cancer in laboratory animals.

Did not cause cancer in laboratory animals.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

Page 25 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Dimethyldimethoxysilane

No relevant data found.

octamethylcyclotetrasiloxane [D4]

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Methyltrimethoxysilane

No relevant data found.

Teratogenicity

Information for the Product:

Product test data not available.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Did not cause birth defects in laboratory animals.

Bis(trimethoxysilyl)hexane

Did not cause birth defects or any other fetal effects in laboratory animals.

3-aminopropyltriethoxysilane

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

methanol

Methanol has caused birth defects in mice at doses nontoxic to the mother as well as slight behavioral effects in offspring of rats.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

Dimethyldimethoxysilane

Has caused birth defects in laboratory animals.

octamethylcyclotetrasiloxane [D4]

Did not cause birth defects or any other fetal effects in laboratory animals.

Methyltrimethoxysilane

Did not cause birth defects or any other fetal effects in laboratory animals.

Page 26 of 52

Revision Date: 20.02.2024 Version: 8.0 Black

Reproductive toxicity

Information for the Product:

Product test data not available.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

In animal studies, did not interfere with reproduction.

Bis(trimethoxysilyI)hexane

In animal studies, did not interfere with fertility.

3-aminopropyltriethoxysilane

In animal studies, did not interfere with fertility.

methanol

In animal studies, did not interfere with reproduction.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

Dimethyldimethoxysilane

In animal studies, has been shown to interfere with fertility.

octamethylcyclotetrasiloxane [D4]

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, has been shown to interfere with fertility.

Methyltrimethoxysilane

In animal studies, did not interfere with reproduction.

Mutagenicity

Information for the Product:

Product test data not available.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and **Methyltrimethoxysilane**

In vitro genetic toxicity studies were positive.

Page 27 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024

Black Version: 8.0

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Bis(trimethoxysilyI)hexane

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

3-aminopropyltriethoxysilane

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

methanol

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative in some cases and positive in other cases.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

Dimethyldimethoxysilane

In vitro genetic toxicity studies were negative.

octamethylcyclotetrasiloxane [D4]

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Methyltrimethoxysilane

In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative.

11.2 Information on other hazards **Endocrine disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Information for components:

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Bis(trimethoxysilyl)hexane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Page 28 of 52

Revision Date: 20.02.2024 Black Version: 8.0

3-aminopropyltriethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

methanol

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Dimethyldimethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

octamethylcyclotetrasiloxane [D4]

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Methyltrimethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data are available.

12.1 Toxicity

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Acute toxicity to fish

No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

For the hydrolysis product(s)

LC50, zebra fish (Brachydanio rerio), 96 Hour, 597 mg/l

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, Daphnia magna (Water flea), 48 Hour, 81 mg/l

Revision Date: 20.02.2024 Black Version: 8.0

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 8,8 mg/l

For the hydrolysis product(s)

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 3,1 mg/l

Toxicity to bacteria

For the hydrolysis product(s)

EC50, Pseudomonas putida, 16 Hour, Growth inhibition, 67 mg/l

Chronic toxicity to aquatic invertebrates

For the hydrolysis product(s)

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, > 1 mg/l

Toxicity to Above Ground Organisms

Material is moderately toxic to birds on an acute basis (LD50 between 51 and 500 mg/kg).

Toxicity to soil-dwelling organisms

NOEC, Eisenia fetida (earthworms), 14 d, >= 1 000 mg/kg

Bis(trimethoxysilyI)hexane

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aguatic plants

EC50, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, > 100 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, > 100 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, activated sludge, Static, 3 Hour, Respiration rates., > 1 000 mg/l, OECD Test Guideline 209

3-aminopropyltriethoxysilane

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Danio rerio (zebra fish), semi-static test, 96 Hour, > 934 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

Page 30 of 52

Revision Date: 20.02.2024 Black Version: 8.0

EC50, Daphnia magna (Water flea), static test, 48 Hour, 331 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aguatic plants

ErC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, > 1000 mg/l

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1,3 mg/l

Toxicity to bacteria

EC50, Pseudomonas putida, 5,75 Hour, Respiration rates., 43 mg/l

methanol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Bluegill sunfish (Lepomis macrochirus), flow-through test, 96 Hour, 15 400 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, > 10 000 mg/l

Acute toxicity to algae/aguatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate, 22 000 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

IC50, activated sludge, 3 Hour, Respiration rates., > 1 000 mg/l, OECD Test Guideline 209

Chronic toxicity to fish

NOEC, Oryzias latipes (Orange-red killifish), 200 Hour, 15 800 mg/l

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Acute toxicity to fish

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

For similar material(s):

LC50, Zebra fish (Danio/Brachydanio rerio), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna, static test, 48 Hour, 39 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aguatic plants

ErC50, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 7.6 mg/l. OECD Test Guideline 201 or Equivalent

For similar material(s):

NOEC, Algae (Scenedesmus subspicatus), Growth rate, 72 Hour, Growth rate, 1,1 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

For similar material(s):

Page 31 of 52

Revision Date: 20.02.2024 Black Version: 8.0

EC50. Bacteria, 3 Hour, Respiration rates., 14 mg/l

Dimethyldimethoxysilane

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on data from similar materials

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 126 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 119 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aguatic plants

Based on data from similar materials

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 118 mg/l, OECD Test Guideline 201

Toxicity to bacteria

Based on data from similar materials

EC50, 3 Hour, > 100 mg/l, OECD Test Guideline 209

octamethylcyclotetrasiloxane [D4]

Acute toxicity to fish

Based on testing of comparable products: The estimated maximum aqueous concentration of Octamethyl Cyclotetrasiloxane (D4) from migration to water from the product as supplied is below the D4 established no-effect threshold (< 0.0079 mg/L) for aquatic organisms.

Chronic toxicity to aquatic invertebrates

Based on testing for product(s) in this family of materials:

Not classified due to data which are conclusive although insufficient for classification.

Methyltrimethoxysilane

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, > 110 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 122 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate inhibition, > 3.6 mg/l. OECD Test Guideline 201

No toxicity at the limit of solubility

NOEC, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate inhibition, >= 3,6 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC10, activated sludge, Static, 3 Hour, Respiration rates., > 100 mg/l, OECD Test Guideline 209

Page 32 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024

Black Version: 8.0

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, >= 10 mg/l

12.2 Persistence and degradability

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and

Methyltrimethoxysilane

Biodegradability: 10-day Window: Fail

Biodegradation: 41,3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not

biodegradable under environmental conditions.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 39 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A or Equivalent

Bis(trimethoxysilyl)hexane

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Fail **Biodegradation:** 74 % **Exposure time:** 28 d

Method: OECD Test Guideline 301B

Stability in Water (1/2-life)

Hydrolyses readily., Hydrolysis, DT50, 5,2 Hour, pH 7

3-aminopropyltriethoxysilane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 67 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A or Equivalent

Stability in Water (1/2-life)

Hydrolysis, half-life, 8,5 Hour, pH 7, Half-life Temperature 24,7 °C

<u>methanol</u>

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Page 33 of 52

Revision Date: 20.02.2024 Black Version: 8.0

Biodegradability: For similar material(s): Material is expected to biodegrade very slowly (in

the environment). Fails to pass OECD/EEC tests for ready biodegradability.

For similar material(s): 10-day Window: Fail

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Dimethyldimethoxysilane

Biodegradability: For similar material(s): Material is not readily biodegradable according to

OECD/EEC guidelines. 10-day Window: Fail **Biodegradation:** 0 % Exposure time: 28 d

Stability in Water (1/2-life)

Hydrolysis, DT50, < 0,6 Hour, pH 7

octamethylcyclotetrasiloxane [D4]

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable **Biodegradation: 3,7%** Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 3,9 d, pH 7, Half-life Temperature 25 °C, OECD Test Guideline 111

Methyltrimethoxysilane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Biodegradation: 54 % Exposure time: 28 d

Method: Regulation (EC) No. 440/2008, Annex, C.4-A

12.3 Bioaccumulative potential

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and

Methyltrimethoxysilane

Bioaccumulation: No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Partition coefficient: n-octanol/water(log Pow): -3,3 Estimated by Structure-Activity

Relationship (SAR).

Bis(trimethoxysilyI)hexane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1,7 at 20 °C Estimated by Structure-Activity

Relationship (SAR).

Page 34 of 52

Revision Date: 20.02.2024 Black Version: 8.0

3-aminopropyltriethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Partition coefficient: n-octanol/water(log Pow): 1,7 at 20 °C Calculated. Bioconcentration factor (BCF): 3,4 Cyprinus carpio (Carp) 56 d

methanol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -0,77 Measured

Bioconcentration factor (BCF): < 10 Leuciscus idus (Golden orfe) Measured

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

Bioaccumulation: No relevant data found.

Dimethyldimethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): Pow: 2 estimated

Bioconcentration factor (BCF): 3,16 Estimated.

octamethylcyclotetrasiloxane [D4]

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and

Partition coefficient: n-octanol/water(log Pow): 6,49 Measured

Bioconcentration factor (BCF): 12 400 Pimephales promelas (fathead minnow) Measured

Methyltrimethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Partition coefficient: n-octanol/water(log Pow): -0.82 Estimated.

12.4 Mobility in soil

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

No relevant data found.

N-(3-(TrimethoxysilyI) propyI)-1,2-ethanediamine

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): > 5000 Estimated.

Bis(trimethoxysilyI)hexane

No relevant data found.

3-aminopropyltriethoxysilane

No relevant data found.

methanol

Partition coefficient (Koc): 0,44 Estimated.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

No relevant data found.

Dimethyldimethoxysilane

Partition coefficient (Koc): 168,6 Estimated.

Page 35 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024
Black Version: 8.0

octamethylcyclotetrasiloxane [D4]

Partition coefficient (Koc): 16596 OECD Test Guideline 106

Methyltrimethoxysilane

No relevant data found.

12.5 Results of PBT and vPvB assessment

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Substance is not persistent, bioaccumulative, and toxic (PBT). Substance is not very persistent and very bioaccumulative (vPvB).

Bis(trimethoxysilyl)hexane

Substance is not persistent, bioaccumulative, and toxic (PBT). Substance is not very persistent and very bioaccumulative (vPvB).

3-aminopropyltriethoxysilane

Substance is not persistent, bioaccumulative, and toxic (PBT). Substance is not very persistent and very bioaccumulative (vPvB).

<u>methanol</u>

Substance is not persistent, bioaccumulative, and toxic (PBT). Substance is not very persistent and very bioaccumulative (vPvB).

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Dimethyldimethoxysilane

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

octamethylcyclotetrasiloxane [D4]

Octamethylcyclotetrasiloxane (D4) meets the current criteria for PBT and vPvB under REACh Annex XIII or other regionally specific criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

Substance is persistent, bioaccumulative, and toxic (PBT).

Substance is very persistent and very bioaccumulative (vPvB).

Methyltrimethoxysilane

Substance is not persistent, bioaccumulative, and toxic (PBT). Substance is not very persistent and very bioaccumulative (vPvB).

12.6 Endocrine disrupting properties The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission

Page 36 of 52

Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Bis(trimethoxysilyl)hexane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

3-aminopropyltriethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

methanol

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Dimethyldimethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

octamethylcyclotetrasiloxane [D4]

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Methyltrimethoxysilane

The substance is not considered to have endocrine disrupting properties according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

12.7 Other adverse effects

Aminopropyltriethoxysilane Rxn with Glycidoxypropyltrimethoxysilane and Methyltrimethoxysilane

Page 37 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst

Revision Date: 20.02.2024 Black Version: 8.0

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Bis(trimethoxysilyl)hexane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

3-aminopropyltriethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

methanol

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Bis[(2-ethyl-2,5-dimethylhexanoyl)oxy](dimethyl)stannane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Dimethyldimethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

octamethylcyclotetrasiloxane [D4]

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Methyltrimethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to ECDirective 2008/98/EC, provided it fulfils the criteria listed in Annex III of this directive. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable 14.4 Packing group Not applicable

Page 38 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024
Black Version: 8.0

14.5 Environmental hazards Not considered environmentally hazardous based on

available data.

14.6 Special precautions for user No data available.

Classification for SEA transport (IMO-IMDG):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

14.5 Environmental hazards Not considered as marine pollutant based on available data.

14.6 Special precautions for user No data available.

14.7 Maritime transport in bulk

according to IMO Consult IMO regulations before transporting ocean bulk

instruments

Classification for AIR transport (IATA/ICAO):

14.1 UN number or ID number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable
 14.4 Packing group Not applicable
 14.5 Environmental hazards Not applicable
 14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACh Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty,

Page 39 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024

Black Version: 8.0

express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75

methanol (Number on list 69, 75)

Bis[(2-ethyl-2,5-

dimethylhexanoyl)oxy](dimethyl)stannane

(Number on list 20)

octamethylcyclotetrasiloxane [D4] (Number on

list 70)

Authorisation status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

CAS-No.: 556-67-2 Name: octamethylcyclotetrasiloxane [D4]

Authorisation status: listed in the Candidate List of Substances of Very High Concern for Authorisation

Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

Further information

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.

Page 40 of 52

H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H410 H412	Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Skin Irrit. - 2 - H315 - Calculation method Eye Dam. - 1 - H318 - Calculation method Skin Sens. - 1 - H317 - Calculation method STOT RE - 2 - H373 - Calculation method

Revision

Identification Number: 4127412 / A282 / Issue Date: 20.02.2024 / Version: 8.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

Logona	
2006/15/EC	Europe. Indicative occupational exposure limit values
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
Dow IHG	Dow Industrial Hygiene Guideline
ES VLA	Spain. Environmental Limits for exposure to Chemical agents - Table 1:
	Occupational Exposure Values
ES VLB	Occupational Exposure Limits for Chemical Agents in Spain - Biological Exposure
	Values
STEL	Short-term exposure limit
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)
VLA-EC	Environmental Short Term Value
VLA-ED	Environmental Daily Limit Value
Acute Tox.	Acute toxicity
Aquatic Chronic	Long-term (chronic) aquatic hazard
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Repr.	Reproductive toxicity
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No

Page 41 of 52

1272/2008: CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS -Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL -No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -(Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA -Toxic Substances Control Act (United States): UN - United Nations: vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL IBERICA S.L. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

Page 42 of 52

Revision Date: 20.02.2024

Version: 8.0

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024 Black Version: 8.0

Annex

Safe Use Information for the Mixture

Number	Title
SUI 1	Formulation or re-packing; Formulation & (re)packing of substances and mixtures
SUI 2	Use at industrial sites; Use in sealants

Lead Component(s)

Component Type	Value Type	Component	State of Matter	Vapour Pressure
Lead substance(s)	aquatic environment	octamethylcyclotetra siloxane [D4]	liquid	93,8362374 Pa
Lead substance(s)	Inhalation	Bis(trimethoxysilyl)h exane	liquid	0,71 Pa
Lead substance(s)	Dermal	Bis(trimethoxysilyl)h exane	liquid	0,71 Pa
Lead substance(s)	Oral	3- aminopropyltriethoxy silane	liquid	0,08 hPa 25 °C
Local effects	Skin	N-(3- (Trimethoxysilyl) propyl)-1,2- ethanediamine	liquid	0,15 kPa 20 °C
		Bis[(2-ethyl-2,5- dimethylhexanoyl)ox y](dimethyl)stannane	liquid	< 1 hPa 20 °C
		3- aminopropyltriethoxy silane	liquid	0,08 hPa 25 °C
Local effects	Eyes	3- aminopropyltriethoxy silane	liquid	0,08 hPa 25 °C
		N-(3- (Trimethoxysilyl) propyl)-1,2- ethanediamine	liquid	0,15 kPa 20 °C
		Aminopropyltriethoxy silane Rxn with Glycidoxypropyltrime thoxysilane and Methyltrimethoxysila ne	liquid	Not available

Risk management measures in section 7, 8 and/or 13 in the main body of the SDS should also be considered.

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024 Black Version: 8.0

SUI1: Formulation or re-packing; Formulation & (re)packing of substances and mixtures

1.1. Title section

Worker		
CS1	Mixing or blending in batch processes	PROC5
CS2	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS3	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)	PROC9

1.2. Conditions of use affecting exposure

1.2.1. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Lead Component Chara	cteristics
Covers concentrations up	to 5%
Amount used (or contain	ned in articles), frequency and duration of use/exposure
Duration	: Covers use up to 4 hrs
Technical and organisat	ional conditions and measures
Provide a good standard	of general ventilation (not less than 3 to 5 air changes per hour).
Provide extract ventilation Inhalation - minimum effic	to points where emissions occur. iency of 90 %
Conditions and measure	es related to personal protection, hygiene and health evaluation
Wear suitable gloves teste Dermal - minimum efficien	
Other conditions affection	ng workers exposure
Indoor or outdoor use	: Indoor use

1.2.2. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Lead (Component	Characteristics
--------	-----------	-----------------

Page 44 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst

Revision Date: 20.02.2024 **Black** Version: 8.0

Covers concentrations up to 100%

Amount used (or contained in articles), frequency and duration of use/exposure

Amounts used 50 L/min

Duration Covers use up to 5 min

Technical and organisational conditions and measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Handle substance within a predominantly closed system provided with extract ventilation. Inhalation - minimum efficiency of 90 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use Indoor use

1.2.3. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Lead Component Characteristics

Covers concentrations up to 5%

Amount used (or contained in articles), frequency and duration of use/exposure

Duration Covers use up to 4 hrs

Technical and organisational conditions and measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Provide extract ventilation to points where emissions occur.

Inhalation - minimum efficiency of 90 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use Indoor use

Page 45 of 52

1.3. Exposure estimation and reference to its source

1.3.1. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Lead Component exposure estimate	Lead Component RCR
inhalative	systemic	long-term	0,011 mg/m³ (ECETOC TRA v3.0 Worker)	0,057
dermal	systemic	long-term	0,014 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,457
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,514

1.3.2. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Lead Component exposure estimate	Lead Component RCR
inhalative	systemic	long-term	0,005 mg/m³ (ECETOC TRA v3.0 Worker)	0,024
dermal	systemic	long-term	0,024 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,8
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,824

1.3.3. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Lead Component exposure estimate	Lead Component RCR
inhalative	systemic	long-term	0,011 mg/m³ (ECETOC TRA v3.0 Worker)	0,057
dermal	systemic	long-term	0,007 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,229
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,286

Not applicable

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024
Black Version: 8.0

1.4. Guidance on the Safe Use Information for the Mixture

This is generic advice on conditions of safe use of a product. When available, this safe use advice is based on Exposure Scenarios provided by raw material suppliers. Following Occupational Health legislation, the employer remains responsible for communicating relevant risk management measures to its employees. When developing workplace instructions for employees, this annex should always be considered in combination with the SDS and the label of the product. Dow shall not be liable and assumes no responsibility for any damages or losses which are the direct or indirect consequence of acts, omissions and/or decisions made full or partly based on the contents of this annex, unless Dow has provided intentionally wrong or incomplete information.

Page 47 of 52

SUI2: Use at industrial sites; Use in sealants

2.1. Title section

Worker		
CS1	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	PROC3
CS2	Transfer of substance or mixture (charging/discharging) at dedicated facilities	PROC8b
CS3	Roller application or brushing	PROC10
CS4	Use as laboratory reagent	PROC15

2.2. Conditions of use affecting exposure

2.2.1. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Lead Component Characteristics				
Covers concentrations up to 5%				
Amount used (or contained in articles), frequency and duration of use/exposure				
Duration : C	covers use up to 15 min			
Technical and organisational conditions	and measures			
Provide a good standard of general ventilated	ion (not less than 3 to 5 air changes per hour).			
Provide extract ventilation to points where emissions occur. Inhalation - minimum efficiency of 90 %				
Conditions and measures related to personal protection, hygiene and health evaluation				
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 95 %				
Other conditions affecting workers exposure				
Indoor or outdoor use : In	door use			

Page 48 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst

Revision Date: 20.02.2024 Black Version: 8.0

2.2.2. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Lead Component Characteristics

Covers concentrations up to 5%

Amount used (or contained in articles), frequency and duration of use/exposure

Duration Covers use up to 15 min

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Handle substance within a predominantly closed system provided with extract ventilation. Inhalation - minimum efficiency of 95 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use Indoor use

2.2.3. Control of worker exposure: Roller application or brushing (PROC10)

Lead Component Characteristics

Covers concentrations up to 5%

Amount used (or contained in articles), frequency and duration of use/exposure

Duration Covers use up to 4 hrs

Technical and organisational conditions and measures

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Handle substance within a predominantly closed system provided with extract ventilation. Inhalation - minimum efficiency of 90 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Page 49 of 52

Indoor or outdoor use Indoor use

2.2.4. Control of worker exposure: Use as laboratory reagent (PROC15)

Lead Component Characteristics

Covers concentrations up to 5%

Amount used (or contained in articles), frequency and duration of use/exposure

Duration Covers use up to 15 min

Technical and organisational conditions and measures

Provide a basic standard of general ventilation (1 to 3 air changes per hour).

Provide extract ventilation to points where emissions occur. Inhalation - minimum efficiency of 90 %

Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %

Other conditions affecting workers exposure

Indoor or outdoor use Indoor use

2.3. Exposure estimation and reference to its source

2.3.1. Worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Exposure route	Health effect	Exposure indicator	Lead Component exposure estimate	Lead Component RCR
inhalative	systemic	long-term	0,001 mg/m³ (ECETOC TRA v3.0 Worker)	0,01
dermal	systemic	long-term	0,007 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,23
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,24

2.3.2. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure	Lead Component	Lead Component
----------------	---------------	----------	----------------	----------------

Page 50 of 52

		indicator	exposure estimate	RCR
inhalative	systemic	long-term	0,011 mg/m³ (ECETOC TRA v3.0 Worker)	0,057
dermal	systemic	long-term	0,011 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,367
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,42

2.3.3. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Lead Component exposure estimate	Lead Component RCR
inhalative	systemic	long-term	0,003 mg/m³ (ECETOC TRA v3.0 Worker)	0,015
dermal	systemic	long-term	0,00034 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,011
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,026

2.3.4. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Lead Component exposure estimate	Lead Component RCR
inhalative	systemic	long-term	0,002 mg/m³ (ECETOC TRA v3.0 Worker)	< 0,01
dermal	systemic	long-term	0,00069 mg/kg bw/day (ECETOC TRA v3.0 Worker)	0,023
combined routes	systemic	long-term	(ECETOC TRA v3.0 Worker)	0,033

Not applicable

2.4. Guidance on the Safe Use Information for the Mixture

This is generic advice on conditions of safe use of a product. When available, this safe use advice is based on Exposure Scenarios provided by raw material suppliers. Following Occupational Health legislation, the employer remains responsible for communicating relevant risk management measures to its employees. When developing workplace instructions for employees, this annex should always be considered in combination with the SDS and the label of the product. Dow shall not be liable and assumes no responsibility for any damages or losses which are the direct or indirect consequence of

Page 51 of 52

Product name: DOWSIL™ 3363 Insulating Glass Sealant Catalyst Revision Date: 20.02.2024 Black Version: 8.0

acts, omissions and/or decisions made full or partly based on the contents of this annex, unless Dow has provided intentionally wrong or incomplete information.

Page 52 of 52